

# velomount 3280

## SUPER-DUTY, HIGH-PERFORMANCE CENTER POST TYRE CHANGER WITH 10" TO 28" CLAMPING

The Centre-Post design secures the rim via a cone and shaft arrangement and is secured into place using a quick-release locking device, leaving the area around the tyre free to work on.

Leverless operation provides the easiest, safest fitting and removal process available, and the StrongArm super-duty assist arm provides all the functions you would expect from a machine of this level, including a lower-bead removal function.

### KEY FEATURES

- Centre post design – no rim damage from clamps
- 10"–28" rim capacity
- Leverless operation
- StrongArm super-duty assist arm
- Ergonomically-positioned bead breaker operating pedal



### SPECIFICATIONS

<b>Rim clamping range:</b>	12" – 28"
<b>Max tyre diameter:</b>	1100 mm – 43"
<b>Max tyre width:</b>	415mm – 16"
<b>Bead breaker cylinder force at 10 bar:</b>	30800 N
<b>Operating pressure:</b>	10 bar (145 Psi)
<b>Power supply:</b>	220V – 1ph
<b>Motor power:</b>	0.75 kW
<b>Net weight:</b>	360 kg (with assist arm)
<b>Max overall dimension (H x W x D):</b>	2020mm x 1200mm x 1830mm (with assist arm)

