

MEGAMOUNT 703E

WHEEL BALANCER

KEY FEATURES

- **Large Turntable Capacity:** Features a 28" turntable with a wide rim external clamping range from 12"-26".
- **Automatic Operation:** Equipped with a pneumatic system for locking the operating arm and a tilting vertical arm controlled by a foot pedal.
- Powerful Hand Operated Bead Breaker: Handoperated via two buttons for ultimate start/stop control, featuring a bead-breaker with a double-effect pneumatic cylinder.
- **User-Friendly Design:** Includes an extractable pedal unit and an oversize body for enhanced stability and ergonomics.
- **Pedal Inflation:** simple accurate tyre inflation at a touch of a pedal.
- Tool Tray: ideal for snap in valves and tyre fitting tools.

THREE-WAY RIGHT ASSIST ARM

- **RFT DOMINATION:** Instantly conquer the stiffest Run-Flat and Low-Profile tyres.
- **TRIPLE-POINT PRECISION:** Three pneumatic tools (disc, rear roller, front arm) work in unison for perfect bead placement.
- **DAMAGE ZERO OPTION:** A lever-less upgrade option is available to guarantee zero rim or tyre damage.
- **FATIGUE ELIMINATED:** Reduces strenuous manual work to a smooth, efficient, one-person process.
- **MAXIMUM THROUGHPUT:** Ensures consistent, accurate mounting for faster service and higher shop revenue.



SPECIFICATIONS

External locking rim dimension	12" - 26"
Internal locking rim dimension	14" - 28"
Max. tyre diameter	1200mm (47")
Max. tyre width	350mm (13.7")
Force on bead breaker blade (10 bar)	3000 kg
Working pressure	8 bar - 10 bar (116 - 145 psi)

Inflating pressure max.	3.5 bar (50 psi)
Power supply voltage (1Ph)	230V
Motor power (1ph)	0.75 kw
Rotating speed	7 rpm
Max. spindle torque	1200 N.m
Noise level in working condition	≤70 db (A)

